

Please rewrite claims 1 and 4 to read as follows:

1. (Twice Amended) A hand operated syringe for injecting liquid, comprising:
a) an elongated barrel having proximal and distal ends and an exit orifice at its distal end;

- b) a pair of opposing finger grips for reception of the index and middle fingers,

respectively, of a user's hand and carried at the proximal end of the barrel, each grip

having a generally distally facing gripping surface having an arcuate portion nearer the barrel than any other arcuate gripping surface portion and defining a most proximal

point on said arcuate gripping surface to which finger pressure is applied proximally

during operation of the syringe, said points defining a plane substantially perpendicular to the barrel's axis;

For: HIGH PRESSURE SYRINGE

- c) a plunger received in the barrel and having a proximal end protruding from the

barrel, said proximal end including a pressure surface adapted to receive manual

pressure; the plunger being movable between retracted and fully inserted positions

within the barrel to discharge a volume of liquid through the exit orifice, the pressure

Assistant Commissioner
for Patents
Washington, D.C. 20231

PRELIMINARY AMENDMENT

Please amend the above-identified application as follows:


IN THE CLAIMS:

Please rewrite claims 1 and 4 to read as follows:

1. (Twice Amended) A hand operated syringe for injecting a liquid, comprising:
- an elongated barrel having proximal and distal ends and an exit orifice at its distal end;
 - a pair of opposing finger grips for reception of the index and middle fingers, respectively, of a user's hand and carried at the proximal end of the barrel, each grip having a generally distally facing gripping surface having an arcuate portion nearer the barrel than any other arcuate gripping surface portion and defining a most proximal point on said arcuate gripping surface to which finger pressure is applied proximally during operation of the syringe, said points defining a plane substantially perpendicular to the barrel's axis;
 - a plunger received in the barrel and having a proximal end protruding from the barrel, said proximal end including a pressure surface adapted to receive manual pressure; the plunger being movable between retracted and fully inserted positions within the barrel to discharge a volume of liquid through the exit orifice, the pressure

BEST AVAILABLE COPY

Please enter 88
1/15/04



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Art Unit 3762
Examiner: R. Stright
Atty. Docket 38943.1.1.1

RECEIVED

MAY 21 2002

TECHNOLOGY CENTER R3700

